

Selectable Wattages: (28W/42W/56W/70W) (48W/72W/96W/120W) (66W/99W/132W/165W)



**WATT/CCT
SELECTABLE**

LED Architectural Wall Pack series can be widely used in indoor or outdoor lighting (wet location). Ideal for museums, art galleries, shopping malls, office buildings, walls and many other applications.

Lighting controls meet design lights consortium (DLC) networked lighting control system technical requirements, LLC, Energy Monitoring and High End Trim function.



FEATURES

- LED high luminous efficiency and long working life.
- High efficiency LED Driver, the wide range input voltage AC120-277V / 277-480V.
- Die-cast aluminum cooling design, high quality and better cooling for LED $T_j < 85^{\circ}\text{C}$.
- Excellent optics design, greatly improve the light utilization and evenness.
- Photocell, Wireless bluetooth system and Motion sensor control available (Optional)
- 12Vdc auxiliary dimming
- The 0-10V Dimming type is continuous.

High performance, die-cast heat sink transfers heat from the light engine to the environment, drawing heat away from the fixture, and extending the lifespan of the LEDs.



Bluetooth®
(Option)

Easy field-install motion sensor

SPECIFICATION

TYPE	SB-AFW2842567W27-345K-D	SB-AFW48729612W27-45K-D	SB-AFW6699132165W27-345K-D
WATTAGE	28W / 42W / 56W / 70W	48W / 72W / 96W / 120W	66W / 99W / 132W / 165W
LUMEN (4000K Type III)	4760 lm / 6880 lm / 8601 lm / 11124 lm	7800 lm / 11288 lm / 14627 lm / 18550 lm	11435 lm / 16481 lm / 21269 lm / 25339 lm
EFFICACY	> 151 lm/W	> 151 lm/W	> 160 lm/W
CCT (Asserted)	3000K, 4000K, 5000K	4000K, 5000K	3000K, 4000K, 5000K
CRI	> 70		
INPUT VOLTAGE	AC120-277V/277-480V		
BEAM ANGLE	Type III: 93.5° X 87.4° (option) / Type IV: 94.3° X 76.8° (option) / Type V: 107.3° X 104.9° (option)		
POWER FACTOR	0.90		
DRIVER EFFICACY	≥89%		
FACTORY SETTINGS	70W & 4000K	120W & 4000K	165W & 4000K
LIFE SPAN	over 50,000 hrs		
WORKING TEMPERATURE	-22°F ~ 113°F		
STORAGE TEMPERATURE	-40°F ~ 176°F		
OUTDOOR RATING	Wet location		
CABLE	3 core, 18AWG (11.8 inch)		
WARRANTY	5 year limited		

Selectable Wattages: (28W/42W/56W/70W) (48W/72W/96W/120W) (66W/99W/132W/165W)

PERFORMANCE

SPECIFICATION																		
TYPE	SB-AFW2842567W227-345K-D-TN																	
POWER	28W (Tested Light Output)									42W (Tested Light Output)								
DISTRIBUTION	TYPE III			TYPE IV			TYPE V			TYPE III			TYPE IV			TYPE V		
CCT	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K
LUMENS	4566	4760	4734	4498	4727	4688	4519	4741	4703	6452	6880	6746	6411	6816	6700	6424	6831	6715
EFFICACY	> 160	> 170	> 165	> 157	> 170	> 163	> 158	> 170	> 164	> 152	> 168	> 158	> 151	> 166	> 157	> 151	> 166	> 157
POWER	56W (Tested Light Output)									70W (Tested Light Output)								
DISTRIBUTION	TYPE III			TYPE IV			TYPE V			TYPE III			TYPE IV			TYPE V		
CCT	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K
LUMENS	7918	8601	8249	7864	8440	8192	7883	8460	8211	9911	11124	10580	9553	10751	10163	9573	10764	10568
EFFICACY	> 146	> 163	> 151	> 145	> 162	> 150	> 145	> 162	> 150	> 140	> 160	> 150	> 135	> 155	> 145	> 135	> 155	> 150


SPECIFICATION													
TYPE	SB-AFW48729612W27-45K-D-TN												
POWER	48W (Tested Light Output)							72W (Tested Light Output)					
DISTRIBUTION	TYPE III		TYPE IV		TYPE V		TYPE III		TYPE IV		TYPE V		
CCT	4000K	5000K	4000K	5000K	4000K	5000K	4000K	5000K	4000K	5000K	4000K	5000K	
LUMENS	7800	7870	7735	7823	7745	7843	11288	11330	11153	11195	11223	11247	
EFFICACY	> 158	> 156	> 157	> 155	> 158	> 156	> 155	> 151	> 153	> 149	> 154	> 150	
POWER	96W (Tested Light Output)							120W (Tested Light Output)					
DISTRIBUTION	TYPE III		TYPE IV		TYPE V		TYPE III		TYPE IV		TYPE V		
CCT	4000K	5000K	4000K	5000K	4000K	5000K	4000K	5000K	4000K	5000K	4000K	5000K	
LUMENS	14627	14487	14429	14324	14505	14366	18550	17974	17873	17373	17342	16869	
EFFICACY	> 151	> 143	> 149	> 142	> 150	> 142	> 155	> 150	> 150	> 145	> 145	> 140	

Selectable Wattages: (28W/42W/56W/70W) (48W/72W/96W/120W) (66W/99W/132W/165W)


PERFORMANCE

SPECIFICATION																		
TYPE	SB-AFW6699132165W27-345K-D-TN																	
POWER	66W (Tested Light Output)									99W (Tested Light Output)								
DISTRIBUTION	TYPE III			TYPE IV			TYPE V			TYPE III			TYPE IV			TYPE V		
CCT	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K
LUMENS	10762	11435	11430	10451	11078	11024	10694	11366	11333	15344	16481	16128	14818	15933	15584	15176	16343	15976
EFFICACY	> 160	> 175	> 170	> 155	> 170	> 165	> 160	> 175	> 170	> 155	> 170	> 160	> 150	> 165	> 157	> 150	> 170	> 160
POWER	132W (Tested Light Output)									165W (Tested Light Output)								
DISTRIBUTION	TYPE III			TYPE IV			TYPE V			TYPE III			TYPE IV			TYPE V		
CCT	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K	3000K	4000K	5000K
LUMENS	19532	21269	20530	19028	20637	19725	19411	21118	20247	23295	25339	23826	22539	24553	23104	23007	25121	23610
EFFICACY	> 145	> 165	> 153	> 143	> 160	> 150	> 145	> 160	> 150	> 140	> 160	> 140	> 137	> 155	> 140	> 140	> 158	> 140

DIMENSION



WATTAGE	28W-70W	48W-120W
NT. WEIGHT	8.14 lbs	8.60 lbs
BOX DIM.	13.58" x 7.87" x 8.27"(1Pcs/CTN)	



WATTAGE	66W-165W
NT. WEIGHT	11.57 lbs
BOX DIM.	16.34" x 9.84" x 9.06"(1Pcs/CTN)

Selectable Wattages: (28W/42W/56W/70W) (48W/72W/96W/120W) (66W/99W/132W/165W)


EMERGENCY BACK-UP (SOLD SEPARATELY)



SB-EMS15W27-XX
SB-EMS20W27-XX
15W/20W Emergency Backup
Battery LED Driver **Low**
voltage (120-277Vac)
Luminaire models



SB-EMS8W27-LT20
8W Low Temperature Emergency
Backup Battery LED Driver
Low voltage (120-277Vac)
Luminaire models
Temperature Rating (Ambient)
-20°C to 60°C (-4 °F to 140°F)




SB-EMS15W27-LT20
15W Low Temperature Emergency
Backup Battery LED Driver
Low voltage (120-277Vac)
Luminaire models
Temperature Rating (Ambient)
-20°C to 60°C (-4 °F to 140°F)



SB-EMS20W27-LT20
20W Low Temperature Emergency
Backup Battery LED Driver
Low voltage (120-277Vac)
Luminaire models
Temperature Rating (Ambient)
-20°C to 60°C (-4 °F to 140°F)

Applicable Luminaire Models: SB-AFW2842567W27-345K-D / SB-AFW48729612W27-45K-D



SB-300YM08W-AC
Emergency Backup Battery LED Driver



SB-300YM15W-AC
15W Emergency Backup Battery LED Driver



SB-300YM20W-AC 8W
20W Emergency Backup Battery LED Driver



SB-300YM25W-AC
25W Emergency Backup Battery LED Driver

Applicable Luminaire Models: SB-AFW2842567W27-345K-D / SB-AFW48729612W27-45K-D / SB-AFW6699132165W27-345K-D

CONTROL (SOLD SEPARATELY)



Bluetooth®
NLC-BT-MW-SR-001
Bluetooth Microwave
Fixture Sensor
(Silvair Bluetooth)



Bluetooth®
NLC-BT-MW-GE-001
Bluetooth Microwave
Fixture Sensor
(GEBC Bluetooth)



NLC-MW-PT-002
Bi-level microwave
Sensor



NLC-PIR-PT-001
Bi-level PIR
Motion Sensor



RC100
Remote Controller
(With NLC-MW-PT-002
and NLC-PC-001 use)



BRI-WS204-GE
4-Button Wireless Wall Switch
(Can only be used for NLC-BT-MW-GE-001)

***MESH RANGE**

60ft node-to-node and 500ft node-to-Gateway (Commissioning)

Selectable Wattages: (28W/42W/56W/70W) (48W/72W/96W/120W) (66W/99W/132W/165W)

PHOTOCELL STANDARD


P (Photocell)

AC277-480V

(No Photocell)

 **Bluetooth®**
(Option)

MOTION SENSOR
and Bluetooth options



Optical lens is made of high quality PC material to make the light even and soft.

WATT/CCT
SELECTABLE




ACCESSORIES:(SOLD SEPARATELY)



SB-165AFW-J-BOX-D
Mounting Base Box

(Suitable for 165W LED Architectural Wall Pack)



Mounting Base Box




ORDERING INFORMATION

EXAMPLE: **SB-AFW2842567W27-345K-D-TN-Y-E** / **SB-AFW48729612W27-45K-D-TN-Y-E**

SB	AFW	2842567W	27	345K	D	TN	Y	E
COMPANY	PRODUCT	WATTAGE	VOLTAGE	CCT	FINISH	DISTRIBUTION	CONTROL	CONTROL
SB LED INC	AFW LED Architectural Wall Pack	2842567W (28W/42W/ 56W/70W) 48729612W (48W/72W/ 96W/120W) 6699132165W (66W/99W/ 132W/165W)	27 (AC120-277V) 48 (AC277-480V)	345K - (3000K/4000K/5000K) 45K - (4000K/5000K)	D - (Dark Bronze) W - (White) B - (Black) S - (Silver)	T3 - (Type III) T4 - (Type IV) T5 - (Type V)	AC120-277V P - (Photocell) AC277-480V (No Photocell)	M - (Motion Sensor)

Selectable Wattages: (28W/42W/56W/70W) (48W/72W/96W/120W) (66W/99W/132W/165W)



NLC-BT-MW-SR-001

Plug and Play Network BLE Nodes and Sensor


The Bluetooth Lighting Control provides automated individual and group control of light fixtures using on sensors and Bluetooth mesh technology. The NLC-BT-MW-SR-001 mounted in an Commercial lighting fixture and provides multi-level control solution based on motion and or daylight harvesting contribution.

FEATURES

- Lighting controls meet design lights consortium (DLC) networked lighting control system technical requirements.
- Quick connect and adjust different sensor angle.
- Easy commissioning with Mobile App (Available in IOS or Android).
- Bluetooth network with Saas working by computer
- Individual addressability and/or grouping.
- Time clock scheduling for individual lights, groups or scenes.
- Multi-level dimming: manual ON/OFF automatic ON/OFF, and automatic partial ON/OFF, daylight harvesting control capability.

SPECIFICATION	
NETWORK BLE MESH	Yes
DAYLIGHT HARVESTING	Yes
MICROWAVE MOTION SENSOR	Yes
DETECTION MODE	Occupancy/Vaccancy/Bi-level in 1 Unit
OPERATING VOLTAGE	12-24V DC
OPERATING CURRENT	>50mA
SINKING CURRENT	max. 25mA
CONTROL OUTPUT	0-10V
RADIO FREQUENCY	2.4GHz ± 75MHz
WIRELESS STANDARD	BLE 5.0 MESH
APP SYSTEM	Silvair iOS App (IOS or Android)
CYBERSECURITY	UL
ENCRYPTION	AES 128-bit
MESH RANGE	60ft node-to-node and 500ft node-to-device (Commissioning)
SAFETY	cULus Listed
FCC	FCC
OPERATING TEMP.	-20°C - +60°C
IP RATING	IP65
WARRANTY	5 year limited

COVERAGE



MICROWAVE SENSOR FEATURES

DAYLIGHT HARVESTING	On/Off
MOTION SENSING	On/Off
FIRST TIME DELAY	1-59 mins/infinite
SECOND TIME DELAY	0-59 mins/infinite
DIM LEVEL	0-100%
MOUNTING HEIGHT	13-40ft
DETECTION RANGE	up to 52ft diameter
DETECTION: HORIZONTAL	360°
DETECTION: VERTICAL	90°

COMMISSIONING

Silvair iOS App or Android makes it easy to pair devices, create groups, set scenes/schedules, customize dimming levels, and adjust high trim based on application needs.

Please scan and download the app.



Operation Instruction:


https://youtu.be/8KWPK7z_Tng

Android:

When using silvair, you can search for silvair in Android Google play to download and install it

Selectable Wattages: (28W/42W/56W/70W) (48W/72W/96W/120W) (66W/99W/132W/165W)

GateWay Remote Control



Functions:

The Silvr Gateway enables the following functions in the Silvr web app:

- Scheduling (available by default)
 - Scheduling changes in scenes and lighting control scenarios (for example occupancy sensing, daylight harvesting) for specific times or days.
- Energy and occupancy monitoring (additional paid service)
 - Visualizing energy use and occupancy via the Silvr web app.
 - Downloading energy and occupancy via the Silvr web app and cloud-based API.
- Remote monitoring and control (additional paid service)
 - Low-latency monitoring of the status of devices in the network via API.
 - Low-latency control of devices in the network via API.
- System diagnostics
 - Monitoring of the status of Bluetooth mesh networks.
 - Remote troubleshooting of networking issues.

Features:

- Future-proof Linux operating system.
- Simple commissioning using the Silvr Commissioning tools.
- Automatic connection to the Silvr cloud.
- Secure provisioning with secure IDs and encrypted keys.
- High level of hardware and software security (secure boot and encrypted file system can only be accessed with the management platform).
- Automatic security updates.
- Prompt releases of OS updates and fixes to vulnerabilities.
- Low-latency transfer of network, luminaire, and sensor status data to the Silvr cloud.
- Schedule caching.
- Automatic remote firmware updates.
- Display of gateway and network performance metrics (requires the Silvr web app).

INDUSTRIAL GATEWAY

SGW-101

Smart Engineering Gateway

The Silvr Gateway connects Bluetooth mesh networks that have been commissioned using the Silvr Commissioning tools to the Silvr cloud. This allows the scheduling of events and delivery of services based on the data generated by these networks.

SPECIFICATION

POWER SUPPLY	4.5–5.5 V DC, 2 A Power over Ethernet 36–57 V DC (IEEE 802.3af)
OPERATING SYSTEM	Ubuntu Core
PROCESSOR	i.MX6ULL (Y2), 32-bit ARM 800 MHz
MEMORY	512 MB DDR3L SDRAM 8GB eMMC
COMMUNICATION PROTOCOLS	Bluetooth mesh (2.4 GHz Bluetooth Low Energy) Wi-Fi 802.11a/b/g/n/ac (2.4/5 GHz) 4G LTE Cat 1 with 2G/3G (only for Cascade-500-W and Cascade-500-X gateways)
PORTS	1 x RJ45 10/100 Ethernet 1 x USB 2.0 Type-A 2 x external dipole antenna, 5 dBi (only for Cascade-500-W and Cascade-500-X gateways)
REQUIRED AMBIENT TEMPERATURE	0°C to 60°C 32°F to 140°F
ENCLOSURE DIMENSIONS	127 mm x 127 mm x 30 mm (5 inch x 5 inch x 1.2 inch)
MOUNTING POSITION	Wall or surface mounted. As close to the geometrical center of the lighting network as possible, but as far as possible from potential sources of interference.
SECURITY	Secure boot with encrypted operating system Secure communication with the Silvr Cloud over Internet (TLS) Secure communication with devices over qualified Bluetooth mesh


Selectable Wattages: (28W/42W/56W/70W) (48W/72W/96W/120W) (66W/99W/132W/165W)

PHOTOMETRICS


For complete IES files, please visit our website.

SB-AFW2842567W27-345K-D-T3 (70W@5000K)


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




CO PLANE ISOLUX DIAGRAM (UNIT:lx)



Flux out: 4000 lm




ISOLUX DIAGRAM




SB-AFW2842567W27-345K-D-T4 (70W@5000K)


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




CO PLANE ISOLUX DIAGRAM (UNIT:lx)



Flux out: 7446 lm




ISOLUX DIAGRAM




SB-AFW2842567W27-345K-D-T5 (70W@5000K)


LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




CO PLANE ISOLUX DIAGRAM (UNIT:lx)



Flux out: 4000 lm



ISOLUX DIAGRAM




Selectable Wattages: (28W/42W/56W/70W) (48W/72W/96W/120W) (66W/99W/132W/165W)

PHOTOMETRICS

For complete IES files, please visit our website.


SB-AFW48729612W27-45K-D-T3 (120W@5000K)

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE(50%):88.4 DEG


CO PLANE ISOLUX DIAGRAM (UNIT:lx)



Flux out: 8500 lm




ISOLUX DIAGRAM




SB-AFW48729612W27-45K-D-T4 (120W@5000K)

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE(50%):75.6 DEG


CO PLANE ISOLUX DIAGRAM (UNIT:lx)



Flux out: 9026 lm




ISOLUX DIAGRAM




SB-AFW48729612W27-45K-D-T5 (120W@5000K)

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE(50%):105.9 DEG


CO PLANE ISOLUX DIAGRAM (UNIT:lx)



Flux out: 12086 lm



ISOLUX DIAGRAM




Selectable Wattages: (28W/42W/56W/70W) (48W/72W/96W/120W) (66W/99W/132W/165W)


PHOTOMETRICS

For complete IES files, please visit our website.

SB-AFW6699132165W27-345K-D-T3 (165W@5000K)



SB-AFW6699132165W27-345K-D-T4 (165W@5000K)



SB-AFW6699132165W27-345K-D-T5 (165W@5000K)

